

# Technical data Overview

	NEOREST WASHLET™ AC	NEOREST WASHLET™ EW	WASHLET™ SG	WASHLET™ GL 2.0 with side or hidden connections	WASHLET™ EK 2.0 with side or hidden connections	
Warm water spray	Comfort spray flow rate	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.27 to 0.43 l/min	0.29 to 0.60 l/min	0.29 to 0.60 l/min
	Soft flow rate	0.32 to 0.43 l/min	0.32 to 0.43 l/min	0.32 to 0.43 l/min	0.29 to 0.58 l/min	0.29 to 0.58 l/min
	Lady shower flow rate	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0.29 to 0.43 l/min	0.29 to 0.60 l/min	0.29 to 0.60 l/min
	Continuous-flow water heater	●	●	●		
	Warm water tank				0.75 l	0.75 l
	Warm water supply	unlimited	unlimited	unlimited	40 seconds	40 seconds
	Adjustable water temperature	30 to 40 °C	30 to 40 °C	30 to 40 °C	30 to 40 °C	35 to 40 °C
	Water tank reheating time				approx. 10 min	approx. 10 min
Comfort	Heated seat, individually adjustable temperature	28 to 35 °C	28 to 35 °C	28 to 36 °C	28 to 36 °C	28 to 36 °C
	Deodoriser – Filter system performance	normal 0.09 m <sup>3</sup> /min, power 0.16 m <sup>3</sup> /min	normal 0.09 m <sup>3</sup> /min, power 0.16 m <sup>3</sup> /min	normal 0.09 m <sup>3</sup> /min, power 0.16 m <sup>3</sup> /min	normal 0.09 m <sup>3</sup> /min, power 0.16 m <sup>3</sup> /min	normal 0.09 m <sup>3</sup> /min, power 0.16 m <sup>3</sup> /min
	Dryer with adjustable temperature	35 to 55 °C approx. 0.29 m <sup>3</sup> /min	35 to 55 °C approx. 0.29 m <sup>3</sup> /min	35 to 55 °C approx. 0.29 m <sup>3</sup> /min	35 to 55 °C approx. 0.27 m <sup>3</sup> /min	35 to 55 °C approx. 0.27 m <sup>3</sup> /min
Connections / Pipes	Power outlet required	●	●	●	●	●
	Water connection pressure	1 to 10 bar	1 to 10 bar	1 to 10 bar	1 to 10 bar	1 to 10 bar
	Power input	1,289–1,527 W	1,289–1,527 W	1,289–1,527 W	278–323 W	278–323 W
	Connection limits	220–240 V / 50 HZ	220–240 V / 50 HZ	220–240 V / 50 HZ	220–240 V / 50 HZ	220–240 V / 50 HZ
Eco	EN 1717 (Drinking water safety)	●	●	●	●	●